



## KA072 5X1 HDMI Switch with 4KX2K@60Hz



### **INTRODUCTION**

This 5x1 HDMI switch routes 5 different sources at resolution up to 4Kx2K@60Hz ultra HD to 1 HDMI display. The unit with 5 HDMI inputs, which makes this unit ideal for simultaneous connection of multiple HDMI devices, such as HDTV, set top box, DVD etc. In addition, this unit with IR receiving window and RS232 port, thus is easy and flexible to control the input signal as you need. It is perfect for security system, medium entertainment, conference exhibition center and digital monitoring system etc.

### **FEATURES**

1. Switch easily between any 5 HDMI source
2. Supports resolutions up to ultra HD 4KX2K@60Hz
3. Supports highest bandwidth up to 18Gpbs
4. Support HDMI 3D
5. Support IR control and RS232 control
6. Plug and play, easy to use
7. Good Compatibility
8. Metal heat sink design, works more stably

Items	Specifications
Input ports	5 x HDMI
Output ports	1 x HDMI
Power indicator led	1 xLED
Signal indicator led	5xLED
HDMI Version	Compatible with DVI1.0, HDMI1.4,HDMI2.0
HDCP Version	Compatible with HDCP1.4,HDCP2.2
Video form	Support 12 bit full HD video, 3D video and 4K×2K@30/60Hz ultra HD video
Input and output TMDS signal	0.5~1.5Vp-p(TMDS)
Input and output DDC signal	5Vp-p(TTL)
Audio	Support standard audio and DSD (Direct Stream Digital) and HD(HBR) audio
HDMI Resolution	480i/480p/756i/756p/720p/1080i/1080p/4K×2K@24/25/30/60Hz
Working temperature	0°C~60°C
Power supply	DC5V/1A
Power consumption	<5W
Dimension	218mm(L)x78.8mm(W)x20.5mm(H)
Weight	420g
Color	Black



